



Physical Dimensions

Model #	Description	A	B	C	D
1P-175-M06-P	Metal Bowl, Manual Drain	4.6	16.75	4.6	2.4
1P-175-M06-F	Metal Bowl, Float Drain	4.6	17.5	4.6	2.4
1P-175-M06-Fi	Metal Bowl, Float Drain w/Indicator	4.6	19.0	4.6	2.4
1P-175-P06-P	Poly Bowl, Manual Drain	4.6	15.0	4.6	2.4
1P-175-P06-F	Poly Bowl, Float Drain	4.6	15.5	4.6	2.4
1P-175-P06-Fi	Poly Bowl, Float Drain w/Indicator	4.6	16.5	4.6	2.4

Specifications

Port Sizes	1/2", 3/4", 1"
Thread Styles	NPT, BSPT, BSPP
Flow Capacity	175 SCFM @ 100 PSI
Bowl Types	Aluminum Polycarbonate
Maximum Temp. & Pressure*	Aluminum 175°F, 200 PSIG Polycarb. 125°F, 150 PSIG
Filter Capacity	3.0 Micron and Larger
Differential Pressure	< 1.0 PSID at Rated Flow

*For higher pressure applications, consult factory. If unit is equipped with differential indicator, maximum temperature and pressure are 125°F and 150 PSIG regardless of bowl design.

Order Guide

	Port Size	Metal Bowl	Metal Bowl w/Indicator	Poly Bowl	Poly Bowl w/Indicator
Manual Drain	1/2"	1P-175-M04-P	1P-175-M04-Pi	1P-175-P04-P	1P-175-P04-Pi
	3/4"	1P-175-M06-P	1P-175-M06-Pi	1P-175-P06-P	1P-175-P06-Pi
	1"	1P-175-M08-P	1P-175-M08-Pi	1P-175-P08-P	1P-175-P08-Pi
Float Drain	1/2"	1P-175-M04-F	1P-175-M04-Fi	1P-175-P04-F	1P-175-P04-Fi
	3/4"	1P-175-M06-F	1P-175-M06-Fi	1P-175-P06-F	1P-175-P06-Fi
	1"	1P-175-M08-F	1P-175-M08-Fi	1P-175-P08-F	1P-175-P08-Fi

Replacement Parts & Accessories

Description	Part Number	Description	Part Number
Bowl O-Ring	N32-95-256	Replacement Element	1P-175
Metal Bowl Assembly, Brass Float Drain	N34-15-179	Blanking Cap	N32-95-020
Differential Indicator	N32-W1-DPi	Manual Drain (for Metal Bowl)	PC-03
Manual Drain (for Poly Bowl)	N32-95-182	Poly Bowl, Brass Float Drain	N32-15-166
Brass Float Drain	N32-95-978		
Plastic Float Drain	N32-95-973		

