



Physical Dimensions

Model #	Description	A	B	C	D
3P-020-M02-P	Metal Bowl, Manual Drain	3.0	6.8	3.0	1.5
3P-020-M02-F	Metal Bowl, Float Drain	3.0	6.8	3.0	1.5
3P-020-M02-Fi	Metal Bowl, Float Drain w/Indicator	3.0	7.5	3.0	1.5
3P-020-P02-P	Poly Bowl, Manual Drain	3.0	6.8	3.0	1.5
3P-020-P02-F	Poly Bowl, Float Drain	3.0	6.8	3.0	1.5
3P-020-P02-Fi	Poly Bowl, Float Drain w/Indicator	3.0	7.5	3.0	1.5

Specifications

Port Sizes	1/4"
Thread Styles	NPT, BSPT, BSPP
Flow Capacity	20 SCFM @ 100 PSI
Bowl Types	Aluminum Polycarbonate
Maximum Temp. & Pressure*	Aluminum 175°F, 200 PSIG Polycarb. 125°F, 150 PSIG
Filter Capacity	1.0 Micron and Larger
Differential Pressure	< 5.0 PSID at Rated Flow

*For higher pressure applications, consult factory. If unit is equipped with differential indicator, maximum temperature and pressure are 125°F and 150 PSIG regardless of bowl design.

Order Guide

	Port Size	Metal Bowl	Metal Bowl w/Indicator	Poly Bowl	Poly Bowl w/Indicator
Manual Drain	1/4"	3P-020-M02-P	3P-020-M02-Pi	3P-020-P02-P	3P-020-P02-Pi
	1/4"	3P-020-M02-P	3P-020-M02-Pi	3P-020-P02-P	3P-020-P02-Pi
Float Drain	1/4"	3P-020-M02-F	3P-020-M02-Fi	3P-020-P02-F	3P-020-P02-Fi
	1/4"	3P-020-M02-F	3P-020-M02-Fi	3P-020-P02-F	3P-020-P02-Fi

Replacement Parts & Accessories

Description	Part Number	Description	Part Number
Bowl O-Ring	N32-95-009	Replacement Element	3P-020
Metal Bowl Assembly, Plastic Float Drain	N32-95-950	Blanking Cap	N32-95-020
Differential Indicator	N32-W1-DPi	Metal Bowl, Manual Drain	N32-95-178
Manual Drain	N32-95-182	Manual Flex Drain	N32-95-610
Brass Float Drain	N32-95-978	Low Flow Plastic Drain	N32-96-400
Plastic Float Drain	N32-95-973	Poly Bowl, Plastic Float Drain	N32-15-160

