



### Physical Dimensions

Model #	Description	A	B	C
1M-2500-MFD-P	3" Manual Drain	20.0	44.75	19.0
1M-2500-MFD-X	3" External Float Drain	20.0	44.75	19.0
1M-2500-MFE-P	4" Manual Drain	20.0	44.75	19.0
1M-2500-MFE-X	4" External Float Drain	20.0	44.75	19.0
1M-5500-MFF-P	6" Manual Drain	20.0	58.5	19.0
1M-5500-MFF-X	6" External Float Drain	20.0	58.5	19.0

*All 1M-2500 units require a minimum 25" clearance between bottom of housing and floor for installation  
All 1M-5500 units require a minimum 36" clearance between bottom of housing and floor for installation*

### Specifications

Port Sizes	3", 4", 6" RFSO
Thread Styles	Raised Face 150# Flanges
Flow Capacity	2500 & 5500 SCFM @ 100 PSI
Bowl Types	Epoxy Coated Carbon Steel
Maximum Temp.	125°F
Maximum Pressure*	150 PSIG
Filter Capacity	3.0 Micron and Larger
Differential Pressure	< 1.0 PSID at Rated Flow

*\*For higher pressure applications, consult factory. If unit is equipped with differential indicator, maximum temperature and pressure are 125°F and 150 PSIG regardless of bowl design.*

### Order Guide

	Port Size	Metal Bowl w/Indicator
Manual Drain	3"	1M-2500-MFD-P
	4"	1M-2500-MFE-P
	6"	1M-5500-MFF-P
Float Drain	3"	1M-2500-MFD-X
	4"	1M-2500-MFE-X
	6"	1M-5500-MFF-X

### Replacement Parts & Accessories

Description	Part Number
Float Drain	N32-95-XD8
Differential Indicator	N32-P2-DPi
Electronic Drain	N32-XED-04
Replacement Element	1X-2500 or 1X-5500

