



## Physical Dimensions

Model #	Description	A	B	C	D
1M-300-M12-DCP	Metal Bowl, Manual Drain	16.5	27.5	7.8	3.9
1M-300-M12-DC	Metal Bowl, Float Drain	16.5	32.0	7.8	3.9
1M-300-M12-DCi	Metal Bowl, Float Drain w/Indicator	16.5	33.0	7.8	3.9
1M-300-M16-DCP	Metal Bowl, Manual Drain	16.5	27.5	7.8	3.9
1M-300-M16-DC	Metal Bowl, Float Drain	16.5	32.0	7.8	3.9
1M-300-M16-DCi	Metal Bowl, Float Drain w/Indicator	16.5	33.0	7.8	3.9

## Specifications

Port Sizes	1-1/4", 1-1/2", 2"
Thread Styles	NPT, BSPT, BSPP
Flow Capacity	300 SCFM @ 100 PSI
Bowl Types	Aluminum
Maximum Temp.	175°F
Maximum Pressure*	200 PSIG
Filter Capacity	0.01 Micron and Larger
Differential Pressure	< 2.5 PSID at Rated Flow

\*For higher pressure applications, consult factory. If unit is equipped with differential indicator or float drain, maximum temperature and pressure are 125°F and 150 PSIG regardless of bowl design.

## Order Guide

	Port Size	Metal Bowl	Metal Bowl w/Indicator
Manual Drain	1-1/4"	1M-300-M10-DCP	1M-300-M10-DCPi
	1-1/2"	1M-300-M12-DCP	1M-300-M12-DCPi
	2"	1M-300-M16-DCP	1M-300-M16-DCPi
Float Drain	1-1/4"	1M-300-M10-DC	1M-300-M10-DCi
	1-1/2"	1M-300-M12-DC	1M-300-M12-DCi
	2"	1M-300-M16-DC	1M-300-M16-DCi

## Replacement Parts & Accessories

Description	Part Number	Description	Part Number
Bowl O-Ring	N32-F35-OR	Electronic Drain	N32-XED-04
Float Drain	N32-95-XD8	2nd Stage Element	3C-300
Differential Indicator	N32-W1-DPi	Blanking Cap	N32-95-020
Manual Drain	KSG-071	1st Stage Element	1M-300

