



Physical Dimensions

Model #	Description	A	B	C	D
1P-060-M04-P	Metal Bowl, Manual Drain	3.8	10.0	3.8	2.0
1P-060-M04-F	Metal Bowl, Float Drain	3.8	10.5	3.8	2.0
1P-060-M04-Fi	Metal Bowl, Float Drain w/Indicator	3.8	11.5	3.8	2.0
1P-060-P04-P	Poly Bowl, Manual Drain	3.8	10.0	3.8	2.0
1P-060-P04-F	Poly Bowl, Float Drain	3.8	10.5	3.8	2.0
1P-060-P04-Fi	Poly Bowl, Float Drain w/Indicator	3.8	11.5	3.8	2.0

Specifications

Port Sizes	1/4", 3/8", 1/2"
Thread Styles	NPT, BSPT, BSPP
Flow Capacity	60 SCFM @ 100 PSI
Bowl Types	Aluminum Polycarbonate
Maximum Temp. & Pressure*	Aluminum 175°F, 200 PSIG Polycarb. 125°F, 150 PSIG
Filter Capacity	3.0 Micron and Larger
Differential Pressure	< 1.5 PSID at Rated Flow

*For higher pressure applications, consult factory. If unit is equipped with differential indicator, maximum temperature and pressure are 125°F and 150 PSIG regardless of bowl design.

Order Guide

	Port Size	Metal Bowl	Metal Bowl w/Indicator	Poly Bowl	Poly Bowl w/Indicator
Manual Drain	1/4"	1P-060-M02-P	1P-060-M02-Pi	1P-060-P02-P	1P-060-P02-Pi
	3/8"	1P-060-M03-P	1P-060-M03-Pi	1P-060-P03-P	1P-060-P03-Pi
	1/2"	1P-060-M04-P	1P-060-M04-Pi	1P-060-P04-P	1P-060-P04-Pi
Float Drain	1/4"	1P-060-M02-F	1P-060-M02-Fi	1P-060-P02-F	1P-060-P02-Fi
	3/8"	1P-060-M03-F	1P-060-M03-Fi	1P-060-P03-F	1P-060-P03-Fi
	1/2"	1P-060-M04-F	1P-060-M04-Fi	1P-060-P04-F	1P-060-P04-Fi

Replacement Parts & Accessories

Description	Part Number	Description	Part Number
Bowl O-Ring	N32-95-257	Replacement Element	1P-060
Metal Bowl Assembly, Brass Float Drain	N34-95-200	Blanking Cap	N32-95-020
Differential Indicator	N32-W1-DPi	Manual Drain (for Metal Bowl)	PC-02
Manual Drain (for Poly Bowl)	N32-95-182	Poly Bowl, Brass Float Drain	N32-15-164
Brass Float Drain	N32-95-978	Poly Bowl, Plastic Float Drain	N32-15-165
Plastic Float Drain	N32-95-973		
Poly Bowl, Manual Flex Drain	N32-95-610		

